

M A T E R I A L S A F E T Y D A T A S H E E T

FAMOWOOD WOOD FILLER - ALL COLORS

PRODUCT NAME: FAMOWOOD WOOD FILLER - ALL COLORS
PRODUCT CODE: 3710101000

HMIS CODES: H F R P
2*3 0 G

48909

SECTION 1 - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ECLECTIC PRODUCTS, INC.
ADDRESS: 995 SOUTH A STREET
SPRINGFIELD, OR 97477
EMERGENCY PHONE: (800) 535-5053
INFORMATION PHONE: (800) 767-4667
DATE REVISED: 6/20/00
DATE PRINTED: 10/26/00
NAME OF PREPARER: MSDS/Compliance Dept.

SECTION 2 - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (mm Hg @ TEMP), WEIGHT PERCENT. Rows include ACETONE, METHYL ETHYL KETONE, DUST, SOLVENT NAPHTHA, Isopropanol, and ZINC STEARATE.

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

DOT Classification: Flammable liquid n.o.s. (contains acetone, methyl ethyl ketone), 3, UN 1993, PGII ERG #128
Limited Quantities (0.3 gallon or less): Consumer Commodity ORM-D

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 133 DEG F
VAPOR DENSITY: Heavier than air.
EVAPORATION RATE: Slower than ether.
APPEARANCE AND ODOR: Colored paste with solvent odor.
SPECIFIC GRAVITY (H2O=1): 1.55
MATERIAL VOC: 2.76 lb/gl
SOLUBILITY IN WATER: NIL

VOC calculations are based on the federal EPA definition of volatile organic compound under the

shown that petroleum distillates may cause kidney, liver or lung damage. Reports have associated related or prolonged overexposure to solvents with permanent brain or nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No **IARC MONOGRAPHS:** Yes **OSHA REGULATED:** No
This product may contain a small percentage of wood dust particles. The International Agency for Research on Cancer (IARC) has classified wood flour as a nasal carcinogen. Sanding or machining cured wood fillers can produce wood dust irritating to the upper respiratory tract and lungs. Avoid breathing dust.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
Persons with severe skin, liver, kidney or lung problems may aggravate these conditions with repeated exposure.

EMERGENCY AND FIRST AID PROCEDURES
EYES: Immediately flush with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention. **SKIN:** Wash skin with soap and water. If irritation occurs, get medical attention. **INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention. **INGESTION:** If swallowed, do not induce vomiting. Call a physician immediately.

===== SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
DANGER. EXTREMELY FLAMMABLE. Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Place in non-leaking containers for proper disposal.

WASTE DISPOSAL METHOD
If this product in its purchased form becomes a waste material, it would be considered a hazardous waste. Dispose of in accordance with local, state, and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Keep away from heat, sparks, and flames. Vapors may accumulate and travel to ignition sources distant from handling site. Keep containers closed when not in use. Use with adequate ventilation. Work station conditions should be evaluated by management to determine proper personal protection and precautions.

OTHER PRECAUTIONS
Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld, or perform similar operations on or near containers. Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers and equipment.

===== SECTION 8 - CONTROL MEASURES =====

RESPIRATORY PROTECTION
If exposure may or does exceed occupational exposure limits, use a NIOSH approved respirator to prevent overexposure. In accordance with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors. Engineering or administrative controls should be implemented to reduce exposure. Dusts may be harmful if inhaled when cured putty is sanded. Wear dust mask.

VENTILATION
Use explosion-proof ventilation as required to control vapor concentrations below recommended levels.

PROTECTIVE GLOVES

Rubber or vinyl-coated gloves are recommended.

EYE PROTECTION

Safety glasses with side shields or goggles as appropriate.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

To prevent repeated or prolonged skin contact, wear impervious clothing. Eyewash fountains and safety showers should be easily accessible and ready for use.

WORK/HYGIENIC PRACTICES

Wash thoroughly after handling, and before eating, drinking, or smoking.

===== SECTION 9 - DISCLAIMER =====

To the best of our knowledge, the information provided herein is accurate, obtained from sources believed to be accurate. Since the conditions and methods of use of our product are beyond our control, we disclaim any and all liability arising out of the improper use of this product or the information provided herewith.